

**BIOXCESS™**



## BFS & BF500

Hybrid Biometric Access Control and Time attendance with Enhanced Visible Light Facial Recognition Terminal



Proactive Facial Recognition



New Height of Anti-Spoofing



Speedy Recognition



Wide Pose Angle Acceptance



Touchless for Better Hygiene

**BIOXCESS** BF500 is a visible light face access control stand-alone terminal. It supports facial recognition and fingerprint with the option to support RFID verification. This series is also equipped with ultimate anti-spoofing algorithm for facial recognition against all types of fake photos and videos attack.


With **BIOXCESS** BFS, you can now create an optimal combination for both In and Out access control, offering the most cost-effective solution.

### Features

- IP65 water and dust resistance (BF500)
- Operating temperature from -5°C to 45°C
- Multiple Verification: Face / FingerPrint / RFID (Optional)
- Available card modules: 125KHz ID card / 13.56MHz IC card
- Fill Light with adjustable brightness

### 2 meters of recognition distance and extra wide angle recognition


The recognition distance has been greatly extended to 2 meters, which significantly improves maximum traffic rate. While most of the algorithms only support +/-15° of detectable face angle, **BF500** doubles the detection angle in terms of head rotation and tilt to +/- 30°.




## Specifications

Display	2.4-inch Touch Screen
Face Capacity	500
Fingerprint Capacity	3,000
Transactions	200,000
Operation System	Linux
Standard Functions	DST, Camera, 14-digit User ID, Record Query, Multiple Verifications Mode
Hardware Specifications	1.2GHz Dual Core CPU 256MB RAM / 512MB Flash 1MP Binocular Camera Adjustable LED Fill Light
Communications	TCP/IP, WiFi (Optional), Wiegand Input / Output, RS485
Access Control Interface	EM Lock, Door Sensor, Exit Button, Alarm Output, Auxiliary Input
Facial Recognition Speed	≤ 1s
Power Supply	12V3A
Operating Humidity	10% - 90% RH
Operating Temperature	-5°C - 45°C
Dimensions (LxWxD)	185x58.5x20 mm

## Configuration



## Optional Accessories



## Dimensions(mm)

